8

9

14 15

16

13

17 18

> 19 20

21 22

23

24 25

CLAIMS

A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job, wherein the source for the Mopy may be selected from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy job wherein the destination for the Mopy may be selected from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destinationselecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to a MFD.

2. A MFD comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 1.

A printer driver comprising a Mopying control system as recited 3. in claim 1.

9

10

11

12

13

14

15

16

17

18

19

20

21


22

23

24

25





- 5. An operating system comprising a Mopying control system as recited in claim 1.
- method facilitating multiple-original-output ("Mopying") 6. control of a Mopy-enabled multifunction device (MFD), the method comprising:

specifying a source for a Mopy in a Mopy job, wherein the source for the Mopy may be one of multiple sources on the MFD;

specifying a destination for a Mopy in a Mopy job wherein the destination for the Mopy may be one of multiple destinations on the MFD.

7. A method as recited in claim 6, further comprising:

formatting a Mopy job, such job includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

transmitting the Mopy job to a MFD.

8. medium having computer-readable computer-executable instructions that, when executed by a computer, performs the method as recited in claim 6.



8

10

11

12

13

V

14 15 16

19

17

18

22

24


25


21

9. A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

in a Mopy job, wherein a source for the Mopy may be selected from multiple sources on the MFD;

- a destination-selection specifier configured to select a destination for each Mopy in a Mopy job, wherein a destination for the Mopy may be selected from multiple destination on the MFD.
 - 10. A system as recited claim 9, further comprising:
- a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for each Mopy in the job and destination-selecting directions for each Mopy in the job;
 - a Mopy-job transmitter configured to transmit the Mopy job to a MFD.
 - 11. A MFD comprising:
 - a printing engine;
 - multiple sources;
 - multiple destinations;
- a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 9.
- 12. A printer driver comprising a Mopying control system as recited in claim 9.





An operating system comprising a Mopying control system as 14. recited in claim 9.